

TATA MOTORS



LPK 2518



Specifications



ENGINE

Engine type	Cummins B180 22
Engine capacity (cc)	5883
Max engine output	131.5 kW at 2250 rpm
Bore / stroke	102 mm x 120 mm
Max engine torque	654 Nm at 1500 rpm
Emission norms	BSIII



TRANSMISSION AND STEERING

Clutch	352 mm, single plate dry friction type
Gearbox	TATA G750 - 6 speed
No. of gears	6F + 1R
1st	8.47
2nd	4.58
3rd	2.73
4th	1.78
5th	1.28
6th	1
Reverse	7.48



FRAME

Type	Ladder type heavy duty frame with rivetted / bolted cross members
Chassis	285 mm x 65 mm x 7 mm
Frame width	888 mm



SUSPENSION

Front	Semi elliptical leaf spring with anti roll bar
-------	------------------------------------------------

Rear	Inverted bogie suspension
------	---------------------------



BRAKE

Service brake	Dual circuit full air S-CAM brake
---------------	-----------------------------------



WHEELS AND TYRES

Tyre size	10.00 x 20-16 PR
-----------	------------------

Wheel rim	7.50 x 20
-----------	-----------

Rear axle	Meritor MT-28-1495 tandem
-----------	---------------------------

Final drive ratio	6.167
-------------------	-------

Front axle	Extra heavy duty forged I beam Reverse Elliot type
------------	----------------------------------------------------



DIMENSIONS

Wheel base	3880
------------	------

TCD	18200
-----	-------

Front track	1964
-------------	------

Rear track	1901
------------	------

Ground clearance	316
------------------	-----

Max. width (wt. body)	2400
-----------------------	------

Overall height (wt. body)	3200
---------------------------	------



WEIGHTS

Max GCW	25000
---------	-------

Max. FAW	6000
----------	------

Max. Raw	19000
----------	-------



PERFORMANCE

Grade ability	24%
---------------	-----

Top speed (kmph)	63
------------------	----



CABIN

Cabin type	Non tiltable
------------	--------------

For more information, please contact:

TATA MOTORS

International Business, One Indiabulls, Tower 2A,
14th Floor 841, S.B Marg, Elphinstone Road,
Mumbai 400 013